X SERIES
HEAVY DUTY GRADE 1 LOCK



Small Format IC
6 or 7 pin



Specification

ANSI:	Meets ANSI - A156.2, Series 4000, Grade 1 Standards
UL Listings:	UL Listed for "A" Label 3 Hour Fire Doors
ADA Compliance:	Meets ADA and ANSI A117.1 accessibility codes
Lock Chassis:	Steel, Zinc dichromated for corrosion resistance
Clutching:	Clutching levers standard for vandal resistance on locking functions
Trim:	5" Solid zinc diecast levers, 3 3/8" wrought brass roses
Lever Return:	Anti-sag mechanism with independent lever return springs to prevent lever sag
Handing:	Non-handed - Completely reversible (S-A & S-B lever styles are handed)
Backset & Latchface:	2 3/4" backset std. with 1 1/8" x 2 1/4" latchface, 2 3/8" backset is available with 1" x 2 1/4" latchface both with self adjusting front for square or beveled edge doors
Latchbolt:	Stainless Steel with 1/2" projection, Deadlocking on keyed functions & exit latch
Cylinder Options:	6 Pin Brass, C Kwy, with 2 Keys std, Prepared for Small format IC core (less core)
Strikes:	4 7/8" x 1 1/4" ASA standard - T strike & Full lip strikes available
Door Preparation:	ANSI A115.2 - 2 1/8" crossbore with (2) 3/8" thru bolt holes
Door Thickness:	Factory Set for 1 3/4" - 1 3/8" require shims, can be adjusted to fit up to 2" thick
Lever Designs:	Flat (standard, shown above), Curved, Half Curved, S-A & S-B
Standard Finishes:	US3 PVD*, US4, US10B, US15, US26 PVD*, US26D (PVD = Lifetime Finish)
Marine Grade Option:	Marine Grade 316 Stainless steel lever and rose cover upgrade available
Fasteners:	Combination screws for wood or metal doors & frames
Warranty:	Limited lifetime warranty